

2-2475E5/ 5HP Duplex / 120 Gallon Tank / 460/3/60

Designed for heavy shop or industrial use, Ingersoll Rand electric-driven, two-stage air compressors provide the reliability and performance that are ideal for most applications including automotive service and body shops, fleet maintenance, machine shops, production and manufacturing lines, wood working shops, dry cleaners, car washes, general maintenance/repair shops and farms.

- **Long-Life:** Durable cast iron construction, long-lasting extended pump life designed for over 15,000 hours of trouble-free use
- **Maximum Power and Flexibility:** 100% continuous duty, 5 or 7.5 hp two-stage air compressor, 175 psig maximum operating pressure and an 80-gallon ASME receiver tank provide plenty of punch for the most demanding applications
- **Easy to Service:** Individually cast cylinders, overhung crankshaft and one piece connecting rod simplifies maintenance and service
- **Reliable Operation:** All Season Select synthetic lubricant increases efficiency; with 2,000 hours of service between changeouts, it performs four times longer than petroleum-based lubricants
- **Two-Year Warranty Available:** Purchase an All-Season Select lubricant start-up kit, and receive all the parts you need for start-up and the first year of maintenance, along with an extended pump warranty



Representative image may not represent quoted product configuration.

Technical Information									
Rated Pressure		Nominal Power		Capacity (FAD)		Dimensions (Length x Width x Height)		Weight (Air-cooled)	
bar g	psig	kW	hp	m ³ / min	cfm	mm	in	kg	lb
12	175	3.7	5.0	0.95	33.6	1778.0 mm, 1117.6 mm, 1092.2 mm	70.0 in, in, 43.0 in	316.8	696.96