

# QT Pro / Pro+ / Max 5-15 | QT-54

When performance and efficiency are in demand, Quincy's QT Series is the premier industrial piston air compressor. The splash-lubricated QT is built with a cast iron body for strength and durability and an aluminum head for optimal cooling and longevity. The QT delivers lasting value through industry leading performance and reliability.



1 Air Filter

2 Splash-lubricated Piston Pump

3 Oil Level Sight Glass

4 Induction Motor

5 Magnetic Starter

6 Pressure Switch and Gauge

7 Drain Valve

8 Receiver

## QT 5-15 HP Reciprocating Air Compressors

### The QT Series Is Best For:

- ✓ Professional and industrial applications requiring premium efficiency and reliability
- ✓ Aluminum head for optimal heat dissipation and increased life-span
- ✓ Available with Pro, Pro+ and Max or fully custom configured models
- ✓ Optimized valve design for the highest volumetric efficiency in the market

## QT MODELS AND CONFIGURATIONS

HP	Phase	Voltage Options	Unit	Tank	Tank Size (Gal)	ACFM (Max Pressure)	RPM	Pump Model	Approx Ship Wt. (lbs)	LxWxH (In)
			Configuration							
3	1	230	Simplex	Vertical	60	10.8 (100PSI)	1180	QTS-3	290	30x23x68
5	1	230	Simplex	Vertical	60	18.4 (100PSI)	1028	QTS-5	345	31x23x68
5	1	230	Simplex	Vertical	60	15.2 (175PSI)	1350	QT-54	350	31x23x70
					80				417	32x26x69
5	1, 3	200, 230, 460, 575	Simplex	Vertical	80	17.2 (175PSI)	658	QT1	565	35x28x77
				Horizontal					595	67x30x49
			Duplex	Horizontal	120	17.2* (175PSI)	658	QT1 (x2)	1115	79x34x54
7.5	1, 3	200, 230, 460, 575	Simplex	Vertical	80	23.6 (175PSI)	896	QT1	595	35x28x77
				Horizontal					630	67x30x49
			Duplex	Horizontal	120	23.6* (175PSI)	896	QT1 (x2)	1180	79x34x54
10S	1	230	Simplex	Vertical	120	27 (165PSI)	1007	QT1	780	37x34x78
				Horizontal					740	71x30x55
			Duplex	Horizontal	200	27* (165PSI)	1007	QT1 (x2)	1555	76x44x63
10S	3	200, 230, 460, 575	Simplex	Vertical	120	29.8 (165PSI)	1192	QT1	780	37x34x78
				Horizontal					740	71x30x55
			Duplex	Horizontal	200	29.8* (165PSI)	1192	QT1 (x2)	1555	76x44x63
10	3	200, 230, 460, 575	Simplex	Vertical	120	36 (175PSI)	682	QT2	945	49x34x78
				Horizontal					890	71x30x55
			Duplex	Horizontal	200	36* (175PSI)	682	QT2 (x2)	2090	76x56x64
15	3	200, 230, 460, 575	Simplex	Horizontal	120	51 (175PSI)	932	QT2	1000	71x30x55
				Horizontal	200	51 (175PSI)	932	QT2	1335	76x56x64
			Duplex	Horizontal	200	51* (175PSI)	932	QT2 (x2)	2315	76x56x64

\*Performance shown per pump on duplex units

Fuel Type	HP	Engine Brand	Tank Configuration	Tank Size (Gal)	Splash Lubricated Model	ACFM @ 175 psig	RPM
Gas	9	Honda	Horizontal	30	QT-54	14.5	1300
Gas	11	Honda			QT1	18.7	622
	13	Honda			QT1	23.6	867
	14	Kohler			QT1	23.6	867
Diesel	10	Yanmar				22.0	800



### QT Pro Package 5-15 hp

- ODP Motor
- Motor Overload Protection
- Ball Valve Tank Drain
- Automatic Start/Stop 5 to 10 hp
- Dual Control on 15 hp
- NO Bull Extended Warranty Available

### QT Pro + 5-15 hp

- ODP Motor
- Motor Overload Protection
- Automatic Tank Drain
- Automatic Start/Stop 5 to 10 hp
- Dual Control on 15 hp
- Low Oil Level Shutdown
- NO Bull Extended Warranty Available

### QT Max Package 5-15 hp

- ODP Motor
- Motor Overload Protection
- Automatic Tank Drain
- Automatic Start/Stop 5 to 7.5 hp
- Dual Control on 10-15 hp
- Low Oil Level Shutdown
- Air Cooled Aftercooler
- NO Bull Extended Warranty Available
- Isolator pads on horizontals



\* Must purchase associated kit at the same time as the compressor to receive warranty extension

## WARRANTY INFORMATION

**NO BULL**

**Optional NO BULL Warranty**



Pro/Pro+/Max Package with Extended Warranty Kit

3-Year Pump/2-Year Package Warranty

OEM Parts/Fluids and Online Registration Required