

QOFT 20-75 HP Series

Set to meet your specific demands and tackle your daily challenges, we offer you the QOFT compressors. Immediately ready to supply high quality oil-free air, this powerful solution provides you with the exceptional reliability and efficiency you are looking for.



1 Inter-cooler & After-cooler

2 Two Stage Tooth Aired

3 Sound Insulated Canopy

4 Induction Motor

5 Air Filter

6 Integrated VSD Inverter

7 Q-Control Touch

8 Electronic Water Drain

QOFT V 20-75 HP Premium Variable Speed

The QOFT V Is Best For:

- ✓ Applications that require compressors to operate at partial loads
- ✓ Customers that are interested in an efficient compressed air system

- ✓ Tooth technology is the most efficient compressor in the industry for its HP range
- ✓ Our QOFT Rotary Tooth Compressors are 50% quieter than Rotary Screw Compressors

QOFT TECHNICAL DATA

Model No.	Working Pressure		Capacity FAD	Installed Motor		Noise Level	Weight		Outlet Size
	Effective	Maximum		kW	HP		Standard		
	psi	psi	cfm			kg	lb		
Aircooled									
QOFT-20	100	109	80	15	20	68	984	2169	1 1/2
QOFT-20	116	125	73	15	20	68	984	2169	1 1/2
QOFT-20	137	145	65	15	20	68	984	2169	1 1/2
QOFT-25	100	109	103	18	25	70	1014	2235	1 1/2
QOFT-25	116	125	97	18	25	70	1014	2235	1 1/2
QOFT-25	137	145	82	18	25	70	1014	2235	1 1/2
QOFT-30	100	109	125	22	30	72	1024	2258	1 1/2
QOFT-30	116	125	114	22	30	75	1024	2258	1 1/2
QOFT-30	137	145	97	22	30	72	1024	2258	1 1/2
QOFT-40	100	109	169	30	40	69	1251	2758	1 1/2
QOFT-40	116	125	162	30	40	69	1251	2758	1 1/2
QOFT-50	100	109	206	37	50	71	1321	2912	1 1/2
QOFT-50	116	125	197	37	50	71	1321	2912	1 1/2
QOFT-60	100	109	241	45	60	73	1341	2956	1 1/2
QOFT-60	116	125	230	45	60	73	1341	2956	1 1/2
Variable									
QOFT-30V	100	145	42-120	22	30	72	1091	2045	1 1/2
	125		41-110						
	145		40-100						
QOFT-50V	100	125	87-214	37	50	71	1386	3056	1 1/2
	125		87-202						
QOFT-75V	100	125	87-302	55	75	73	1386	3056	1 1/2
	125		87-294						

(1) Unit performance measured according to ISO 1217, Annex C, Edition 4 (2009)

Model No.	Standard		
	A	B	C
	Length (mm/in)	Width (mm/in)	Height (mm/in)
QOFT-20-25-30	1760/69.3	1016/40	1620/63.8
QOFT-40-50-60	2006/79	1016/40	1880/74
QOFT-30V	2195/86.4	1016/40	1620/63.8
QOFT-50V-75V	2440/96.1	1016/40	1880/74



WARRANTY INFORMATION

STERLING BLUE

Sterling Blue 2-year Extended



2-year Airend warranty
 12 month bumper-to-bumper coverage
 Authorized start-up required and Quincy Genuine Parts & Fluids must be used

Sterling Blue Guardian 3-year Extended

3-year Airend, Coolers, Motor Drive & VSD Warranty (Parts & Labor)
 18 month bumper-to-bumper coverage
 Only Genuine Quincy Compressor maintenance & replacement parts may be used
 Authorized Startup Required